

Tank Range

# STURDY OIL TANKS



Sturdy Compact Tank

Capacity:950L

Length:1650mm

Width:675mm

Height:1000mm

Product Code:067- A



Sturdy R Tank

Capacity:1100L

Length:1650mm

Width:675mm

Height:1130mm

Product Code:004- A



Sturdy 1000 Tank

Capacity:1100L

Length:1725mm

Width:1050mm

Height: 1000mm

Product Code:001- A



Sturdy 1,300L Tank

Capacity:1360L

Length:1725mm

Width:1150mm

Height:1100mm

Product Code:002- A



Sturdy JXL Tank

Capacity:2500L

Length:2100mm

Width:1350mm

Height:1330mm

Product Code:069- A



Sturdy 2,000 Tank

Capacity:2220L

Diameter:1930mm

Height:1290mm

Product Code:175- A





Sturdy 3,000Tank

Capacity: 3300L

Diameter:

1930mm

Height: 1670mm

Product Code 174- A



Sturdy 5000 Tank

Capacity: 5000L

Diameter: 1930mm

Height: 2380mm

**Product Code** 

059- A



Sturdy 10,000 Tank

Capacity: 10,100L

Diameter: 2500mm

200011111

Height: 2815mm

**Product Code** 

365- A



# URDY BUNDED TANKS





# Sturdy Rectangular Bund

Capacity: 1210L

Length: 1900mm

Width: 800mm

Height:

1350mm

**Product Code** 242- A



# Sturdy Horizontal Bund

Capacity: 1495L

Length: 2000mm

Width:

1270mm

Height: 1220mm

**Product Code** 339-A



# Sturdy JXL Bund

Capacity: 2750L

Length:

2400mm

Width: 1700mm

Height: 1490mm

**Product Code** 150-A



# Sturdy 2,400 It Bund

Capacity: 2420L

Diameter: 2210mm

Height:

1350mm

**Product Code** 292- A



# Sturdy 3,500 lt Bund

Capacity: 3630L

Diameter: 2210mm

Height:

1740mm

**Product Code** 291-A



#### 5,500 lt Bund

Capacity: 5500L

Diameter:

2210mm

Height: 2460mm

**Product Code** 290- A



#### 11,000 lt Bund

Capacity: 11,000L

Diameter: 2640mm

> Height: 2890mm

**Product Code** 368-A



# STURDY WATER TANKS



| \ | Sturdy 290L  | Sturdy 390L  | Sturdy 450L  |
|---|--------------|--------------|--------------|
|   | Water Tank   | Water Tank   | Water Tank   |
|   | Capacity:    | Capacity:    | Capacity:    |
|   | 290L         | 390L         | 450L         |
|   | Length:      | Length:      | Length:      |
|   | 805mm        | 980mm        | 1040mm       |
|   | Width:       | Width:       | Width:       |
|   | 570mm        | 570mm        | 570mm        |
|   | Height:      | Height:      | Height:      |
|   | 860mm        | 860mm        | 860mm        |
|   | Product Code | Product Code | Product Code |
|   | 216- A       | 215- A       | 214- A       |



Sturdy 300L Hydro-Boost Water Tank

Capacity: 300L

Diameter: 560mm

Height: 1380mm

Product Code 629- A



| Sturdy 850L            |
|------------------------|
| Water Tank             |
| Capacity:<br>850L      |
| Length:                |
| 1000mm                 |
| Width:                 |
| 675mm                  |
| Height:                |
| 1610mm                 |
|                        |
| Product Code<br>456- A |



| Sturdy 950L<br>Water Tank |
|---------------------------|
| Capacity:<br>950L         |
| Length:<br>1650mm         |
| Width:<br>675mm           |
| Height:<br>1000mm         |
| Product Code<br>067- W    |



| Sturdy 1000L<br>Water Tank |  |
|----------------------------|--|
| Capacity:<br>1000L         |  |
| Length:<br>1725mm          |  |
| Width:<br>1050mm           |  |
| Height:<br>1000mm          |  |
| Product Code<br>001- W     |  |



| Sturd<br>Water |      |
|----------------|------|
| Capa<br>110    |      |
| Leng           | ıth: |
| 1650           | mm   |
| Wid            | th:  |
| 675r           | nm   |
| Heig           | ht:  |
| 1130           |      |
| Product        | Code |
| 004-           | W    |




| Sturdy 1300L<br>Water Tank |  |
|----------------------------|--|
| Capacity:<br>1360L         |  |
| Length:                    |  |
| 1725mm                     |  |
| Width:                     |  |
| 1150mm                     |  |
| Height:                    |  |
| 1100mm                     |  |
| Product Code               |  |
| 002- W                     |  |
|                            |  |



| Capacity:<br>2500L     |  |
|------------------------|--|
| Length:<br>2100mm      |  |
| Width:<br>1350mm       |  |
| Height:<br>1330mm      |  |
| Product Code<br>069- W |  |

Sturdy 2,500L Water Tank





#### Sturdy 2,000L Water Tank

Capacity:

Diameter: 1930mm

> Height: 1290mm

Product Code 171- A



#### Sturdy 3,000L Water Tank

Capacity: 3300L

Diameter: 1930mm

Height: 1670mm

Product Code 170- A



#### Sturdy 5,000 L Water Tank

Capacity: 5000L

Diameter: 1930mm

Height: 2380mm

Product Code 268- A



#### Sturdy 10,000 Water Tank

Capacity: 10100L

10100L

Diameter: 2500mm

Height: 2815mm

Product Code 366- A



#### 1250L Water Tank (Underground)

Capacity: 1250L

Length:

1875mm

Width: 1640mm

Height: 600mm

Product Code 418- A

### Sturdy Rainwater Harvesting Tank 1250 Lt

The Rainwater Harvesting Tank harvests the natural resource of rainwater thus reducing your mains water costs while promoting an eco-friendly solution.

The water collection tanks low profile design along with the integrated columns gives it excellent load bearing strength, which has been tested up to sustain 4 tonnes when empty. Its low profile means that shallow hand dug excavations are suitable. It can also pass through doorways or side passage ways. When situated in ones garden lawns can be replaced on top of the Rainwater Harvesting Tank.



# Technical Specifications:

Capacity: 850L

Width:

675mm

Length: 1000mm

Height: 1610mm

> Code: 519-A

GARDEN

This 850L Water Storage Tank is ideal for collecting rainwater specifically for watering your garden.

The rainwater is collected through a downpipe diverter which directs it into the storage tank. The diverter also acts as an overflow once the tank becomes full.

The rectangular shape of the tank allows it to fit neatly into corners or against walls, causing you the minimum amount of intrusion.



## **STURDY** Tank Plinths

The Sturdy Storage Tank Support Plinths offer an ideal and secure support base for your Oil Storage Tank or Water Storage Tank, ensuring a longer life.

- There are two different plinth models available, a cylindrical version and a flat version.
- Both plinths are designed to take the load of all Sturdy Tanks up to 5000lt in capacity.
- Manufactured to exacting standards and detailed specification using UV stabilised medium density polyethylene the plinths are extremely strong
- They are relatively maintenance free as they do not need to be painted and will never rust or rot
- The plinths are available in a range of standard colours to meet your requirements.



Flat Plinth

Width: 1400mm Length: 1980mm Height: 400mm

Code: 168 - A

#### **Cylindrical Plinth**

Width: 1870mm Length: 1980mm Height: 700mm

## STURDY Fuel Pod

The STURDY Fuel Pod is a fully enclosed pumping station designed specifically to house a fuel pump, hose kit and nozzle.

 The unit accommodates the Sturdy Metering Pump and Hose Dispenser, which are sold separately

• The Fuel Pod suitable for the complete range of Sturdy Products Tanks and range Bunds.

As an optional extra your company name can be printed on the Fuel Pod Pumping 

Station to help promote your company.

lockable system is available as an optional extra.



**Technical Specifications** 

Width: 590mm Length: 900mm Height: 990 mm

Code: 414 - A

Code: 167 - A

# **STURDY** Apollo Contents Gauge

The Sturdy Apollo Oil Gauge is the most reliable oil tank gauge on the market

- The Apollo Gauge uses a high quality FM signal to send out tank readings to a receiver placed in your home or office.
- It is easy to install and can be ready for use within minutes.
- This Apollo Gauge is a universal tank gauge, meaning that it can be fitted to any size or shape of tank up to 3 metres in height.
- The Gauge shows levels of fuel in your tank as a 10 bar display on the receiver.
- The transmission range is 200m and the transmitter contains a tried and tested long life lithium battery.

**Technical Specifications** 

Tank Depth Measurement: Min. Depth: 0,1 m, Max. Depth: 3 m Code: 335 - A

## **STURDY** Metering Pump and Hose Dispenser

The Sturdy Metering Pump and Hose Dispenser has been developed for the distribution of diesel fuel.

- priming rotary vein pumps with incorporated by-pass valve.
- Motor with protection grade IP55 and thermal protection, 230V AC single phase.
- Three meters of antistatic rubber hose for fuel.
- Automatic type dispensing nozzle with on-off switch incorporated into the nozzle rest and fitted with a shut-off device for full tanks.
- The flow-meters mounted on pumps have sturdy mechanical readout systems whose reliability and easiness to use have been proved by time.
- Simple and versatile, CUBE pumps can also be installed on drums, thanks to their 1"

**Technical Specifications** 

Width: 378mm Length: 430mm (incl. nozzle) Height: 297mm Code: 380 - A

## STURDY Bund Alarm

- Bund Alarm provides an early warning of a breach in the bund layer of the tank.
- Should a significant amount of fluid get between the tank and the bund the unit will emit a 90dB warning alarm.
- It is available in battery and mains options.
- The battery operated version has PP3 9v Battery.
- The unit is provided with a liquid detection probe.
- The system is also available for use as an overfill alarm or as a bund and overfill alarm combined.



**Technical Specifications** 

Width: 110mm Length: 60mm Height: 110mm

Code: 443 - A



### STURDY 2" Fill Stop

- The Sturdy Fill Stop is a universal design which fits metal or plastic tanks utilising fitting accessories included in kit
- It terminates in a hard-anodised 2" BSP Parallel thread, suitable for direct connection to filling tanker
- For use with thin viscosity petroleum fuels, such as
- Each Valve is tested in accordance with EN13616:2004

- Performance;
  Maximum Flow 580 Ipm
  Minimum Flow 23 Ipm
  Leakage Rate </2.5 Ipm</li>

- Maximum Filling Pressure 8 bar Minimum Filling Pressure 0.15 bar Maximum Pressure Surge 12 bar Thread Size / Type 2" BSP Parallel Male




**Technical Specifications** 

Overall Diameter: 82mm Overall Height: 245 mm

Code: 450 - A

### **STURDY** Sight Gauge

- The Sturdy External Sight Gauge gives a clear reading of the level of contents in a storage tank
- It is suitable for fitting to most storage tanks and can be supplied in lengths to suit any depth storage tank.
- It has an unbreakable sight gauge and can be used with heating oil, paraffin and diesel.
- The top cap protects against insects and dust. The top clip provides upper support for the sight tube and it is supplied with self tapping fixing screws.
- A control valve should always be fitted at the outlet first. This is not supplied with the External Sight Gauge, however it can be supplied as an optional extra.



**Technical Specifications** 

Suits Standard 1" BSP Connections. Max. Height - 1830mm

Code: 442 - A

## **STURDY** Access Platform

- The Sturdy Tank Access Platform and Ladder gives access to the top of large storage tanks.
- The fill inlet, valves, content level gauges and other structures, to which the tank operator must have access in order to fill the tank with liquid, are usually located on the topmost surface of the large storage tank.
- The tank operator needs to have a safe and secure access to the top of the tank to fill the tank and to adjust or repair the controls when required.
- The Tank Access Platform and Ladder is designed to provide a safe vertical path between the ground and a flat work platform attached to the ladder at the top of the tank.
- Guardrails are provided to enhance the safety of the platform. It can be ground anchored by use of anchor bolts.



#### **Technical Specifications**

Single Platform Double Platform Code: 381 - A Code:395-A

## **STURDY** Sturdy Dispensing Hose & Nozzle Kit

- The Sturdy Dispensing Hose and Nozzle Kit is appropriate for dispensing small quantities of diesel fuel, paraffin or light oils.
- It is of strong design and can be used in arduous situations
- The gate valve can be supplied with a locking bracket if required.
- The gate valve and hose are 1" as standard.
- The hose is available in 3m lengths as standard however longer lengths are available upon request.
- The hose itself is diesel resistant with a nylon reinforcement.





**Adblue Option** 

**Technical Specifications** 

1" x 3m Hose as Standard

Code: 018 - A

## **STURDY** Scully Contents Gauge

- The easy to install Scully Contents Level Gauge works perfectly under all weather conditions
- It eliminates inaccurate readings and it can be used if the storage tank is indoor or
- It reads if the storage tank is full, 3/4, 1/2, 1/4 or empty.
- The exposed part of the gauge is galvanised to help prevent againt rusting.
- The Scully Gauge is suitable for 1.5" 2"



**Technical Specifications** 

Suitable for Tanks with a minimum height of 27".

Code: 142 - A

## **STURDY** Adblue Pump

- The Sturdy Adblue Pump is ideal for pumping the chemical Adblue from a storage tank into a vehicle.
- Adblue is a non toxic solution used in the exhaust system of Euro4 or Euro5 trucks to reduce harmful emissions
- AdBlue is sprayed into the exhaust manifold where it breaks-down and reacts with the exhaust gases and turns eco-friendly nitrogen.
- Trucks registered in the EU are required to be compliant with exhaust emissions regulations. Most trucks engines therefore require SCR technology which uses Adblue.
- Pump Specification370W Electric Pump
  - **Digital Meter** 
    - Automatic inox nozzle
- Meter Accuracy: +/- 1%

**Technical Specifications** 

4m Delivery Hose as Standard with a Flow Rate of 40L/min.

Code: 451 - A





# STURDY PRODUCTS LIMITED

Blessington Industrial Estate, Blessington, Co. Wicklow, Ireland

Tel: +353 (0)45 865044

Fax: +353 (0)45 865721

E-mail: sales@sturdyproducts.com Website: www.sturdyproducts.com

Looking forward to hearing from you.

